

Ballistic Coating.

PERFORMANCE BENEFITS

- Provides a hard, durable coating over many wall surfaces, over 8,500 PSI (typically 9,000+ PSI) compressive strength (Per ASTM C109)
- Applies directly over gypsum board, EPS foam, existing stucco, cement board, CMU blocks or wood substrates using mesh impregnated.
- Noncombustible building material (Per ASTM E136)
- Zero flame spread, and zero smoke developed indices (Per ASTM E84)
- Resistant to mold and mildew growth (Per ASTM G21)
- When applied over EPS foam meets ICC building code required fire protection requirements (Per UBC 26-3; NFPA 286; and IBC Section 803.2.1, Corner Room Fire Tests).
- Meets all the emission level requirements of the GREENGUARD Product Quality.
- Can be applied to create both smooth and textured finishes; and, it can be painted.
- Pre-formulated mix, needs only mixing on site, nothing to add.
- Mix and apply using pumps/sprayers or troweled by hand.

QTY.	Packaging	Applied Thickness	Coverage	lbs/sqft	Protection
1	75-lb bag	5/8"	12 sqft/bag	6	Hand Gun
1	75-lb bag	3/4"	9.25 sqft/bag	7	Hand Gun
1	75-lb bag	7/8"	9 sqft/bag	8	Hand Gun
1	75-lb bag	1"	7.5 sqft/bag	10	Hand Gun, Rifle
1	75-lb bag	1.5"	5 sqft/bag	15	Rifle
1	75-lb bag	2"	3.75 sqft/bag	20	Rifle

Distributed Nation Wide By: Guardian Security Structures LLC.

1.406.212.2334 rg@gssdoors.com www.gssdoors.com Discount Code GSS91